



SANITIZING RANGE



I N D U S T R I A L A N D S T R E E T C L E A N I N G E Q U I P M E N T

HYDRO – STREET WASHERS

Dulevo street washers range, used for the cleaning, hygienisation and sanitation of roads, is available in Electric, Natural Gas (CNG) and traditional Diesel powered versions.

The machines, with 4 steering wheels or articulated chassis with central joint, guarantee maximum maneuverability during the work phase. The water tanks are made in stainless steel AISI 304, therefore it's possible to mix different disinfectant products inside them. The machines can be configured, according to customer needs, with high pressure systems, automatic dosing systems for the sanitizing product and with rotating arm for the simultaneous work of two operators (Washing



AISI 304 Stainless Steel Water Tank

Extendable washing bar

Side nozzles

High-pressure system with reel and water gun

Turning Arm

Dosing system for chemical product / disinfectant



AISI 304 Stainless Steel Water Tank

Extendable washing bar

Side nozzles

High-pressure system with reel and water gun

Turning Arm

Dosing system for chemical product / disinfectant



AISI 304 Stainless Steel Water Tank

Extendable washing bar

Side nozzles

High-pressure system with reel and water gun

Turning Arm

Dosing system for chemical product / disinfectant

TECHNICAL DATA		D.ZERO ² HYDRO	6000 HYDRO CNG	6000 HYDRO
Washing width with bar	in (mm)	70,9 (1800)	110,24 (2800)	110,24 (2800)
Washing width with extendable bar	in (mm)	110,24 (2800)	125,98 (3200)	125,98 (3200)
Place in the cabin	N°	2	2	2
Working cycle - Indicative cleaning performance	ft ² (m ²)/water tank	177.604,52 (16500)	236.806,02 (22000)	322.917,3 (30000)
Clean water tank capacity	Gal (Lt.)	396,26 (1500)	1.162,36 (4400)	1.558,62 (5900)
Powered		BATTERY LI FE P04	CNG (NATURAL GAS)	DIESEL
Maximum speed	mph (Km/h)	15, 53 (25)	15,53 - 24,85 (25 - 40)	15,53 - 24,85 (25 - 40)
Dimensions (L x W x H)	mm	4835 x 1480 x 2300	5240 x 2190 x 3270	5070 x 2190 x 3270
Dimensions (L x W x H)	in	190,35 x 58,27 x 90,55	206,3 x 86,22 x 128,74	199,61 x 86,22 x 90,55

COMBI – SWEEPERS AND WASHERS

The Dulevo range also offers machines for combined use. The machines combine the functions of sweeping and washing / sanitizing. The machine, with a single operator and directly from the cabin, can sweep and wash / sanitize at the same time. The machine can also be used in combined mode by two operators (Sweeping and washing with operator on the ground).



Polyethylene tank

High-pressure system with reel and water gun



AISI 304 Stainless Steel Water Tank

High-pressure system with reel and water gun



Extendable washing bar

Turning Arm



AISI 304 Stainless Steel Water Tank

High-pressure system with reel and water gun



Extendable washing bar

Turning Arm

TECHNICAL DATA		BOOST COMBI	3000 COMBI	6000 COMBI	7500 COMBI	8000 COMBI
Washing width	in (mm)	47,24 (1200)	74,8 (1900)	82,68 (2100)	98,43 (2500)	98,43 (2500)
Sweeping width	mm	1450	2750 ÷ 2900	2600 ÷ 3500	2200 ÷ 2700	2200 ÷ 2700
Sweeping width	in	57,09	108,27 ÷ 114,17	102,36 ÷ 137,8	86,61 ÷ 106,3	86,61 ÷ 106,3
Gross volume capacity of the hopper(UNI EN 15429-1)	yd ³ (m ³)	0,26 (0,2)	0,26 (3)	7,19 (5,5)	7,85 (6)	10,46 (8)
Place in seats	Nº	1	2	2	2	2
Clean Water tank capacity	gal (Lt.)	58,12 (220)	192,85 (730)	277,38 (1050) ÷ 303,8 (1150)	554,76 (2100)	792,52 (3000)
Powered		Electric-Diesel-Petrol -LPG	Diesel	Diesel	Diesel	Diesel
Maximum speed	mph (Km/h)	3,73 - 4,35 (6 - 7)	15,53 - 24,85 (25 - 40)	15,53 - 24,85 (25 - 40)	55,92 (90)	55,92 (90)
Length	in (mm)	86,68 (2100)	165,35 (4200)	204,33 (5190)	242,52 (6160)	274,02 (6960)
Width	in (mm)	44,25 (1200)	81,89 (2080)	92,52 (2350)	100,39 (2550)	100,39 (2550)
Height	in (mm)	55,91/83,86 (1420/2130)	105,12 (2670)	128,74 (3270)	125,98 (3200)	129,92 (3300)

SCRUBBER DRYER RANGE

Dulevo scrubber dryers offer a targeted and customized solution for all cleaning and sanitizing needs. The wide range offers machines walk behind, able to satisfy the cleaning of the small and medium surfaces and narrow space, and ride on, normally used in environments such as airports, large shopping center, industries and warehouses.



DATI TECNICI		20.0	30.0	50.0	90.0	110.0	150.0	300.0	
Scrubbing path	mm	430	450	500 ÷ 600	650 ÷ 850	550 ÷ 680	680 ÷ 836	1000 ÷ 1200	
Scrubbing path	in	16,93	17,72	19,69 ÷ 23,62	25,59 ÷ 33,46	21,65 ÷ 26,77	26,77 ÷ 32,91	39,37 ÷ 47,24	
Squeegee path	mm	440	670	750	890 ÷ 980	775 ÷ 870	870 ÷ 1045	1300 ÷ 1470	
Squeegee path	in	17,32	26,38	29,53	35,04 ÷ 35,58	30,51 ÷ 34,25	34,25 ÷ 41,14	51,18 ÷ 57,87	
Max.Cleaning performance	m ² /h	1720	1800	2000 ÷ 2400	3250 ÷ 4250	3200 ÷ 4000	4000 ÷ 5000	7000 ÷ 8400	
Max. Cleaning performance	yd ³	2.057,1	2.152,8	2.392 ÷ 2.870,4	3.887 ÷ 5.083	3.827,2 ÷ 4.784	4.784 ÷ 5.980	8.371,9 ÷ 10.046,3	
Clean water tank	gal (Lt)	4,5 (17)	7,93 (30)	13,21 (50)	23,78 (90)	27,74 (105)	39,63 (150)	79,25 (300)	
Recovery tank	gal (Lt)	5,3 (20)	7,93 (30)	13,21 (50)	20,34 (77)	30,38 (115)	44,91 (170)	73,97 (280)	
Traction		MANUAL - BRUSH ASSISTED / ELECTRIC				ELECTRIC			
Power source		CABLE / BATTERY				BATTERY			



HIGH PRESSURE SYSTEM



All models of the street range can be fitted with high-pressure systems, complete with gun and reel hose. With the high pressure gun, it is possible to clean the most inaccessible corners, remove dirt even from vertical surfaces and walls and can be used to keep the machine clean.





DULEVO INTERNATIONAL S.P.A.
Via G.Guareschi,1 - 43012 - Fontanellato (Parma) Italia
ph: +39 0521 827711 - Fax: +39 0521 827795
info@dulevo.com - www.dulevo.com

